


**D3/4/5/6/8/1057/30CJ 超薄崁燈系列**


崁孔 70MM



崁孔 95MM



崁孔 130MM



崁孔 155MM



崁孔 195MM



崁孔 230MM

**Specufucations:**

Model	D357/3008CJ	D457/30BJ	D557/30BJ	D657/30BJ	D657/30BJ5	D857/30BJ	D1057/30BJ5	D1057/30BJ
Input	AC100~240V							
Power Consumption	6W	8W	10W	12W	15W	20W	25W	30W
Power Factor	>0.9							
CCT	5700/3000K	5700/3000K	5700/3000K	5700/3000K	5700/3000K	5700/3000K	5700/3000K	5700/3000K
CRI	80							
Luminous Flux(lm)	520/410	770/615	920/730	1060/850	1340/1080	1790/1430	2020/1610	2370/1890
Beam Angle	100°							
Operating Temperature	-20°C~50°C							
Operating Humidity	20%~90%							
Dimensions(Φ x H)	80x30mm	110 x30mm	150 x30mm	180x30mm		210 x30mm	245x30mm	
Recess Diameter	70mm	95mm	130mm	155mm		195mm	230mm	
Weight	115g	170g	290g	380g		480g	700g	
Certifications	BSMI/CE/IEC62471							
Made in	Taiwan							