



- ▶ Dimension \varnothing 49mm
- ▶ CRI(Ra) >85
- ▶ Working Temp. -20~+40°C



MR1657/40/30/2705/07CH30/60 Nichia MR16 GU5.3 Series

| Color | Lamp Base | Input | Power | Color Temperature | | | | Beam Angle |
|--------|-----------|-------|-------|-------------------|-------|-------|-------|------------|
| | | | | 2700K | 3000K | 4000K | 5700K | |
| Silver | GU5.3 | AC12V | 5W | 2700K | 3000K | 4000K | 5700K | 30°/60° |
| Black | | DC12V | | 310LM | 330LM | 360LM | 400LM | |



MR1657/40/30/2708CU21/40 Nichia MR16 GU5.3 Series

| Color | Lamp Base | Input | Power | Color Temperature | | | | Beam Angle |
|--------|-----------|-------|-------|-------------------|-------|-------|-------|------------|
| | | | | 2700K | 3000K | 4000K | 5700K | |
| Silver | GU5.3 | AC12V | 7W | 2700K | 3000K | 4000K | 5700K | 30°/60° |
| Black | | DC12V | | 594LM | 623LM | 667LM | 741LM | |

Note:4000K is acceptable by customize demend.

Advantages

- ▶ **No flicker**
- ▶ **Recyclable**
- ▶ **Double insulation**
- ▶ **Short circuit protection**
- ▶ **Overloading protection**
- ▶ **Overheating protection**
- ▶ **Over voltage protection**

Features

| | | |
|-----------------------|----------------------------|-----------------|
| | | |
| Power Efficiency | Power Factor | NICHIA LED |
| | | |
| Superior Optical Lens | Patented Thermal Radiation | Lightest Weight |