



SRNXXABXX Solar Light series

Common Specifications :

Input	DC12~24V
Ingress Protection	IP66(Light) ; IP65(Solar Panel & Connector)
CCT	5000K(3000K,6000K available)
Beam Angle	149°×72°/145°×(17°+55°)15°/30°/60°/30°×15°
Street Light Insert Diameter	φ 50~65mm
Light Operating Temperature	-30°C~50°C(Light) ; -40°C~85°C(Solar Panel & Connector)
Certifications	Power : CE/CB/PSE/UL ; Light : CE/CB
Guarantee	Light : 2 years ; Solar Panel & Connector : 5 years

Specifications :

Model No.	SRN30ABST	SRN60ABST
Lm	2700	5400
Lm/W	90	
Power Input	30	60
Solar Panel	100W	2×100W
Solar Charge Controllor	DC12V/24V 10A	
Lead-acid Battery	DC12V 100AH	2×DC12V 100AH
Working Time	3 days(10 hrs/day)	
Peak Shine Hour	5 hrs/day average	
Weight	2.7Kg(Light) ; 8.2Kg(100W Solar panel)	4.7Kg(Light) ; 8.2Kg(100W Solar panel)
Dimensions	446*150*128(Light) ; 1200*550*35(Panel)	377*305*128(Light) ; 1200*550*35(Panel)
Picture		
Model No.	SRN30ABFL	SRN60ABFL
Lm	2700	5400
Lm/W	90	
Power Input	30	60
Solar Panel	100W	2×100W
Solar Charge Controllor	DC12V/24V 10A	
Lead-acid Battery	DC12V 100AH	2×DC12V 100AH
Working Time	3 days(10 hrs/day)	
Peak Shine Hour	5 hrs/day average	
Weight	2.7Kg(Light) ; 8.2Kg(100W Solar panel)	4.7Kg(Light) ; 8.2Kg(100W Solar panel)
Dimensions	244*305*128(Light) ; 1200*550*35(Panel)	340*305*128(Light) ; 1200*550*35(Panel)
Picture	