

T59/18C/N/YBC1/2 T5LED 可調光燈管系列



燈管直接輸入 AC110V 或是 AC220V 即可點亮，若是做間接照明層板燈用途，須串接專用串燈空盤(內無變壓器)，每一迴路可串接 10 支；可適用 TRIAC 調光器無段式調光。

Specifications :

Model	T59/18CBC1/2		T59/18NBC1/2		T59/18YBC1/2	
Input	AC 110V,0.096A(2ft),0.186A(4ft)/ AC 220V,0.048A(2ft),0.093A(4ft)					
Power Consumption	2ft:9.3W/4ft:18.1W					
Power Factor	0.88					
Base	G5					
LED Quantity	2ft:SMD 3020× 80pcs /4ft:SMD 3020× 160pcs					
CCT	5650K		4000K		3000K	
CRI	70		75		80	
Beam Angle	120°					
Length	2ft	4ft	2ft	4ft	2ft	4ft
Luminous Flux	550±40	1080±40	490±40	940±40	460±40	870±40
Illuminance@1M	118 Lux	220 Lux	100 Lux	190 Lux	94 Lux	175 Lux
Operating Temperature	-20~40°C					
Dimensions	Diameter:15.6mm; Length 2ft:549mm/4ft:1149mm					
Weight	105g(2ft)/200g(4ft)					

注意事項 Notes :

◎安裝前請先移除起動器

Remove starter before installation

◎安裝前須先確認輸入電壓

Checking system input voltage match products before installation

◎注意：本產品不可使用在電子安定器燈具上

Do not use at system connected with electronic stabilizer

<http://www.new-wonder.com.tw> Tel:(02)2821-8897 Fax:(02)2821-4997