

T89/18C/N/YBC1/2 T8 LED 可調光燈管系列



燈管直接輸入 AC110V 或是 AC220V 即可點亮，若是做間接照明層板燈用途，須串接專用串燈空盤(內無變壓器)，每一迴路可串接 10 支；可適用 TRIAC 調光器無段式調光。

Specifications :

| Model | T89/18CBC1/2 | | T89/18NBC1/2 | | T89/18YBC1/2 | |
|-----------------------|---|---------|--------------|---------|--------------|---------|
| Input | AC 110V,0.096A(2ft),0.186A(4ft)/ AC 220V,0.048A(2ft),0.093A(4ft) | | | | | |
| Power Consumption | 2ft 9.3W/4ft 18.1W | | | | | |
| Power Factor | 0.88 | | | | | |
| Base | G13 | | | | | |
| LED Quantity | 2ft:SMD 3020× 80pcs/4ft:SMD 3020× 160pcs | | | | | |
| CCT | 5650K | | 4000K | | 3000K | |
| CRI | 70 | | 75 | | 80 | |
| Beam Angle | 120° | | | | | |
| Length | 2ft | 4ft | 2ft | 4ft | 2ft | 4ft |
| Luminous Flux(Lm) | 550±40 | 1080±40 | 490±40 | 940±40 | 460±40 | 870±40 |
| Illuminance@1M | 118 Lux | 220 Lux | 100 Lux | 190 Lux | 94 Lux | 175 Lux |
| Operating Temperature | -20~40°C | | | | | |
| Dimensions | Diameter:24.6mm; Length 2ft:580mm/4ft:1198mm | | | | | |
| Weight | 180g(2ft)/320g(4ft) | | | | | |