



TLNAB series Tunnel Light

Common Specifications :

Input	AC100~277V, 50~60Hz
Power Factor	(AC100~240V)>0.9 ; (AC277V)>0.8
Ingress Protection	IP66
CCT	5000K(3000K,6000K available)
Beam Angle	149°×72°/145°×(17°+55°)15°/30°/60°/30°×15°
Insert Diameter	φ 50~65mm
Operating Temperature	-30°C~50°C
Power Certifications	CE/CB/PSE/UL
Light Certifications	CE/CB
Guarantee	2 years

Model No.			TLN075AB	TLN060AB	TLN113AB	TLN090AB
LED Source			CREE	NICHIA	CREE	NICHIA
Lm			6000	5400	9000	8100
Lm/W			80	90	80	90
Power Input			75	60	112.5	90
Weight			6.5Kg		8.8Kg	
Dimensions			279×280×156.5mm		374.5×280×156.5mm	
Picture						
Model No.	TLN150AB	TLN120AB	TLN188AB	TLN150AB	TLN225AB	TLN180AB
LED Source	CREE	NICHIA	CREE	NICHIA	CREE	NICHIA
Lm	12000	10800	15000	13500	18000	16200
Lm/W	80	90	80	90	80	90
Power Input	150	120	187.5	150	225	180
Weight	11.1Kg		13.4Kg		15.7Kg	
Dimensions	470×280×156.5mm		565×280×156.5mm		662×280×156.5mm	
Picture	